

RVS dompelpompen

Europese top producten



Afmetingen:

Type	Diameter	Hoogte
Turbo 50	154 mm	249 mm
Turbo 80	154 mm	249 mm
AX800(v)	160 mm	325 mm
MX800(v)	160 mm	325 mm
RS 400	167 mm	275 mm
RS 400 (v)	167 mm	275 mm

Bestel nr.	Type	Watt	Hp	Vuil doorlaat	Cap.Max.	H.max.	Gewicht	Volt	Aansl	€ excl. BTW	Datablad
pd50	Turbo 50	250	0,33	10 mm	10 m ³ p/uur	8 m	5 kg	230	1 1/4"	220,-	
pd50v	Turbo 50+vlotter	250	0,33	10 mm	10 m ³ p/uur	8 m	5 kg	230	1 1/4"	235,-	
pd80	Turbo 80	450	0,60	10 mm	12 m ³ p/uur	10 m	6 kg	230	1 1/4"	240,-	
pd80v	Turbo 80+vlotter	450	0,60	10 mm	12 m ³ p/uur	10 m	6 kg	230	1 1/4"	255,-	
pdax800	AX 800	600	0,80	5 mm	16 m ³ p/uur	9 m	7 kg	230	1 1/2"	289,-	
pdax800v	AX 800+vlotter	600	0,80	5 mm	16 m ³ p/uur	9 m	7 kg	230	1 1/2"	294,-	
pdmx800	MX 800	600	0,80	25 mm	15 m ³ p/uur	8 m	7 kg	230	1 1/2"	305,-	
pdmx800v	MX 800+vlotter	600	0,80	25 mm	15 m ³ p/uur	8 m	7 kg	230	1 1/2"	315,-	
pdmx800mv	MX 800+mousvlotter	600	0,80	25 mm	15 m ³ p/uur	8 m	7 kg	230	1 1/2"	342,-	
pd-rs400	RS 400	400	0,50	10 mm	15 m ³ p/uur	11 m	13 kg	230	2"	325,-	
pd-rs400v	RS 400+vlotter	400	0,50	10 mm	15 m ³ p/uur	11 m	13 kg	230	2"	375,-	